

# GOVERNMENT

# Swiftpro K60 Double Sided

# **Retransfer Card Printer**

KIS Global provides market-leading solutions with an extensive range of retransfer desktop solutions to meet the needs of the customer and by adding value to global businesses. Our mission to revolutionise business identity and access management by building trusted partnerships through our simple SMART™ partner distribution networks.

The Swiftpro K60D retransfer card printer has an outstanding print quality for single and double sided printing. With 600dpi printing density, it is the ideal solution for businesses requiring high-quality identification cards, passes, and badges with personalized physical and logical access management.

The ultra-fast, powerful Swiftpro K60D printer is available with contact and contactless smart card encoding technologies and 100 cards input and output hopper with optional 250 hopper upgrade. This reliable and durable printer is the ideal solution for both entry level to advanced secure card programs for a range of vertical markets.

Selecting the right printer is important, more important is ensuring the supply of Genuine Swiftpro Supplies and Retransfer film is also critical in delivering reliability, print quality and vibrant colours for your card programs. Swiftpro supplies deliver consistency and ensure the longevity of your printer and print head and minimize downtime and create efficiencies in your card programs. Always ask for Genuine Swiftpro Supplies from your Authorised Premiere Value Added Distributor, Premiere

Value Added Distributor, Premiere Enterprise Solution Provider or Premiere Value-Added Reseller.



### **SECURITY**

The ribbon erase function prevents leakage of personal information on the monochrome panel ink ribbon. It scrambles information beyond recognition to protect this data.



# **VERSATILITY**

Swiftpro's modular design permits customers to upgrade as their card programs need changes.



# **IMAGE QUALITY**

High Resolution printing using 600dpi printing provides superior print quality for all your card programs.



# **RELIABILITY**

Swiftpro K-Series are well respected globally for their Japanese engineering for quality and reliability.



# INNOVATION

Innovating since the 90's with state of the art retransfer printers, providing safe, secure, and reliable ID card printer solutions to global organizations since 1989.



IDENTITY CARD

A.B.B1,C,CE,C1E,D,C

# **DURABILITY**

Highly durable printers with industry leading warranties on all our products and lifetime on the print head.



Pioneering **SMART**<sup>™</sup> Business Operations



Dye Sublimation Retransfer

Full Color Retransfer printing

Single and Double Sided Printing

Up to 130 Cards Per Hour (YMCK) up to 70 Cards Per Hour (YMCKK)

256 Graduation Printing

Over the Edge Printing on CR80, ID-1 Cards

**USB & Ethernet connectivity** 

100 Input Hopper (30mil)

100 Output Hopper (30mil)

LCD Panel

600 DPI Print Resolution

36 Month Printer Warranty

Lifetime Printhead Warranty

Microsoft Certified Drivers

Solenoid Electronic Locks for Input Hopper

Solenoid Electronic Locks for Supplies / Front Door Housing

Controlling Lock/Unlock from Status Monitor

K Ribbon Erase Function

IpSec Security for Secure Data Encryption IPv6 and IPv4

Inline Bend Remedy

MAC Address Forced Printing (UV Panel on Card)

Kensington Locks



KIS Global GmbH

Oststrasse 34, Duesseldorf Germany 40211
T: +49-211-3689-255 E: channel@kisglobal.com www.kisglobal.com

Via Grassilli, 11 - 40012 Calderara di Reno (BO) T: +39 051-757040 E: info@ermes-online.it

Magnetic Stripe ISO High/Low Coercivity Encoder

Contactless Encoder, Omnikey 5127 (iClass, Mifare and Desfire)

Contact Encoder (CF-7CRW / Control board)

Contact Encoder (CF-7CCS / IC Contact Station)

CardPresso

Card Exchange

All Card Personalisations software used through Swiftpro Driver\*

\*check with Software vendor and some feature may be limited for use on Swiftpro Printers

Microsoft® Windows® 7, 8, 10 32bit / 64bit

Microsoft® Windows® Server 2008 R2 (SP1) 64bit

Microsoft® Windows® XP Server 2012 64bit

YMCK - 1000 Yield

YMCKK - 750 Yield

YMCKP Peel Off Ribbon - 750 Yield

YMCKU UV - 750 - Yield

InTM Retransfer Film - 1000 Yield

Height	335mm	Without Card Stacker
Width	343mm	Without Card Stacker
Depth	322mm	Without Card Stacker
Weight	13.5 KG	

USB2.0 (Hi-speed / Full Speed)

Ethernet (100BASE-TX / 10BASE-T)

Flipper Unit

Bend Remedy

Temperature: 15°C to 30°C

Humidity: 35% to 70% (YMCK ink, No Condensation)

3.5A (100V system) 1.6A (220V system)

310W (maximum power when all options are installed)

Card Thickness 10-40mil

Card Size ISO 7810 Format, CR80, ID-1

Card Material: PVC, PC, PET, PET-G

Technology Cards Contact and or Contactless with and Without Mag Stripe

