

# CSNBOWA DP 01 TS

## HIGH SECURITY PAPER SHREDDER AND BRIQUETTING SYSTEM

The CSNBOWA DP 01 TS specifically designed for professional environments and TOP confidential paper destruction; through its solid hardened steel crushing module it is able to shred the paper material from 15 x 15 mm up to 2x2 mm. with the 01TS NBR model is possible to insert up to 100 pages (70G) in a single time.

Compliance with safety requirements of CE, equipped with PLC Control, dust filtering, vacuum system, overload material sensor, secure key lock for cabinet door open/closed, sound proof and dust proof closed housing.

The CSNBOWA DP 01 TS NBR shredding module is a shredder solution that meets DIN 66399 security level P5-P7 and the guidelines regarding the physical destruction of data contained on paper support. The system can also be equipped or upgraded with Briquetting system to reach the highest security level in the market.



PAPER



BANKNOTE



CHEQUE  
CHEQUES



CLIP



FOLDER



### USED BY

- ▶ Banks
- ▶ Government bureau
- ▶ Police and Military DPT
- ▶ Security bureau

### IDEAL FOR

- ▶ Paper
- ▶ Banknote
- ▶ Cheques
- ▶ Voucher

## Technical specifications CSNBOWA DP 01TS\*

### SHREDDING MATERIAL

Shreddable material



Paper



Folder



Clips



Cheques  
Voucher



Banknote

### SECURITY LEVEL

Security Level

P-5

P-6

P-7

Screen size (diameter mm)

15\*15 - 8\*8 - 2,5\*2,5

### PERFORMANCE

Output per hour

50 kg-120 kg

Single shredded paper volume

80- 100 sheets at a time (80g)  
100 – 120 sheets at a time (70g)

Inlet size

300mm\*196mm

### HARDWARE

Cutting Module

Single Shaft cutting stage with net  
knife screen

Filtering

9 m<sup>2</sup> each 320(D) \*900(H)mm  
Vacuum and Dust filter included

Waste bag volume

400 liters

Power/ Voltage/frequency

7,75 kw/(3-phase, 380V)/50-60Hz

Controller

PLC

Noise Level

75-85 DB

Machine size

1880(L) x1020(W) x 1900(H) mm

Machine Weight

724 kg

Certification

CE

Warranty

12 months



## Technical specifications 01TS HYDRAULIC BRIQUETTING SYSTEM\*

Hydraulic briquetting system

DRY briquetting process

Briquette Size

50mm (D) x 30-50 mm (H)

Discharge port

Single

Oil Tank

85 Lt

Power/ Voltage/frequency

3,75 kw/(3-phase, 380V)/50-60Hz

Briquetting system size (mm)

2500 (L) x 900 (W) x 1300 (H)

Weigh

584 Kg

Certification

CE

Warranty

12 months



\*Manufacturer reserve the right to modify/ upgrade the specification at any time



DEPEI INTERNATIONAL SRL

distributed by

### Ermes srl

Via Grassilli, 11 - 40012 Calderara di Reno (BO)

Tel.: +39 051 757040 - Fax: + 39 051 6160441

e-mail: [info@ermes-online.it](mailto:info@ermes-online.it)

[www.ermes-online.it](http://www.ermes-online.it)